NXT-2201P36

Cloud Paging Amplifier



SPON Cloud Paging Amplifier NXT-2201P36 embedded with SPON's proprietary intellectual property, the IP Audio digital network audio technology features a compact 1U size with optimal 350W constant voltage power output. With a digital amplifier chip for higher efficiency, it includes a built-in backup system to ensure continuous stable operation.

Cloud Control | Scenario Presets | Fault Alarm | Offline Control

MAIN FEATURES



1.Simple design to reduce non-specialized operations and lower maintenance issues.

2.It features 1 emergency microphone input and 4 front analog inputs, with independent volume adjustment for each audio channel.

3.Provides a constant 100V output with an efficiency of over 90%.

4.Supports offline operation. When the network is interrupted, it can automatically switch to local playback.It can store multiple sets of configurations and run them automatically based on dates.

5.Supports one-click configuration and configuration saving through an app, allowing for remote real-time control and remote updates of scheduled tasks and ringtone files.

SPECIFICATION

POWER PARAMETERS

Power Supply:	AC 220V, 50Hz
Rated Output:	360W
Power Current:	5A

AUDIO PARAMETERS

S/N (Signal-To-Noise) Ratio:	MIC:>85dB;AUX:>95dB ;
Audio Sampling & Bit Rate:	48kHz, 24bit
THD (Total Harmonic Distortion):	≤0.5% At 1kHz, 1/2 Rated Output
Frequency Response:	130Hz~18KHz

NETWORK PARAMETERS

Network I/F:	10BASE-T/100BASE-TX RJ45
Network Protocol:	HTTP, RTP, TCP/IP, UDP, ARP, ICMP, IGMP
Configuration Method:	Web Interface Or AIXT-APP

MECHANICAL&ENVIRONMENT PROPERTIES

Mounting Method:	1U Rack-Mounted
Installation Environment:	Dry Indoor Locations Only
Operating Temperature:	-10℃~+50℃
Operating Humidity:	+90% RH Non-Condensing
Heat Dissipation:	Intelligent Temperature Control, Forced Air Cooling
Protection:	Over-Current Protection, Short-Circuit Protection, Overload Protection, Over-Temperature Protection, Lightning Protection, Surge Protection
Housing Material:	Surface-Treated Steel Plate
Color:	Black
Product Dimensions:	483×334×44mm
Product Weight:	4.87Kg
Product Warranty:	2 Years

ACCESSORIES

1× Adapter (6.35 To 3.5)
1× RCA Audio Cable (1.5 Meters)
2× Mounting Brackets
8× Countersunk Cross Screws (M4×6)
4× Foot Pads (Ø23.9X6.3M Adhesive)
1× Power Cord (1 Piece, 3×1.0mm2(1.5mm2)Optional)
1× Wire Terminal (7.62-4P-5S)
4× Wire Terminals (3.81-4P)
1× Certificate Of Compliance And Warranty Card
1× Quick Installation Guide

INTERFACE DESCRIPTION

[Front Panel]




① Up Page Button ② Down Page Button ③ USB Interface

[Rear Panel]



④ Dynamic Microphone Input Interface (default to hot-plug, user-customizable)
⑤ Safety Grounding Terminal
⑥ Fuse Holder Built-in replaceable fuse tube
⑦ Line Input Interface (4 channels)
⑧ Power Output Interface
⑨ Power Input Interface: AC220V Power Input
⑩ Network Interface
⑪ FM Antenna Interface
⑫ Alarm Output Interface (4 channels)
⑬ Alarm Input Interface (4 channels)

CONNECTION DIAGRAM



APPLICATIONS

Application 1

SPON NXT-2201P36 Cloud Paging Amplifier is suitable for chain stores, convenience stores, private residences and other scenes .It is plug and play device ,after it register to the cloud server ,user can use mobile to manage at everywhere in the world.



INSTALLATION

RACK MOUNT

Note: Please prepare the rack-mounting screws separately.

DESKTOP MOUNT

The materials used from the accessory kit
Ø1.2*3 (foot pads) X4

SPON SPON Communications Co., LTD

Address: No.70, Nantang Road, High-Tech Zone, Changsha, China. **Mobile:** +86 139 7314 3517
Email: inquiry@sponcomm.com **Tel:** +86 731 8557 0190

For more information