

XC-9037NV

IP Video Intercom Master Station

SPON IP Video Intercom Master Station XC-9037NV is a network high-fidelity video intercom paging microphone based on TCP/IP, SIP, USP and other transmission protocols.It can realize visual, intercom, paging and control operations.It has the characteristics of beautiful appearance, comfortable paging control, convenient operation and one-button call. Signal digital transmission design, intelligent control as the core.

Voice PoE SIP WiFi Bluetooth

MAIN FEATURES

1.Display and Audio Features

- 7-inch high-definition capacitive touch screen with 800×1280 resolution.
- Built-in digital audio processor for full duplex and hands-free audio intercom.
- Integrated 2 MP HD digital camera with physical privacy protection.





2. Broadcasting and Communication

- Supports file, pre-recorded, and TTS broadcasting to specific zones or terminals.
- Enables initiating and receiving offline calls between multiple devices.
- Compatible with standard SIP protocol for easy integration with mainstream SIP PBX systems (Yeastar, Asterisk, Cisco, etc.).
- Customizable ringtones for incoming calls and broadcasts.



3.Monitoring and Call Management

- Online monitoring of other terminals' working status, aiding in debugging and maintenance.
- Features for recording, tracking, and querying incoming and outgoing calls.



SPECIFICATION

POWER PARAMETERS

Power Supply:	DC5V 3.5A or POE(IEEE802.3at/af)
Standby Power Consumption:	<10W

AUDIO & VIDEO PARAMETERS

Audio Codec:	MP3, PCM, ADPCM
Audio Sampling & Bit Rate:	8KHz-44.1KHz, 16bit, 64Kbps-320Kbps
Built-in Speaker:	3W, 4Ω
S/N:	>80dB
Frequency Response:	40Hz-18KHz
Camera:	2 Million Pixels
Video Transmission Bit Rate:	512Kbps-4Mbps
Video Codec:	VGA/720P/1080P

NETWORK PARAMETERS

Network Transmission Rate:	100Mbps
Network Protocol:	TCP/IP, UDP, ARP, ICMP, IGMP, HTTP, SIP
Configuration Method:	Web Interface Or DevConfig Tool

MECHANICAL&ENVIRONMENT PROPERTIES

Display Screen:	7 inch(1280×800)Touch Color LCD Screen
Mounting Method:	Desktop
Installation Environment:	Dry Indoor Locations Only
Operating Temperature:	0°C~+40°C
Operating Humidity:	<90% RH Non-Condensing
Housing Material:	ABS
Color:	Black
Product Dimensions:	183.9×169.0×54.4mm
Product Weight:	0.7KG
Product Warranty:	2 Years

ACCESSORIES

1×Quick Installation Guide

1×Terminal Block(3.5MM)

1×Certificate And Warranty Card

1×Microphone Rod(M 32/80

PORTS DESCRIBTION



① **Rods Socket :** Plug the microphone rods to collect sounds

② **Speaker:** Receives the remote and local sounds.

③ **Indicator Light:** Lightning during video intercom.

④ **Camera:** Collect local video.

⑤ **Touch Screen**



⑥ **Power Input Port :** Connect with DC12V/1.5A power adaptor.

⑦ **USB Port:** Store the audio/txt file for broadcast.

⑧ **Network Port :** To connect with RJ45 or None-PoE switch.

⑨ **Relay Output Port :** To connect with strobe light , buzzer ,etc.

⑩ **Audio Input Port :** To connect with mobile phone or laptop ,etc.

⑪ **Relay Input Port :** To connect with emergency button ,etc.

⑫ **Audio Output Port :** To connect with active speaker or amplifier.

INTERFACE DESCRIPTION



APPLICATIONS

Application 1

IP Video Intercom Master Station XC-9037NV can initiate and receive video & audio intercom with the 3rd party VOIP telephone , SPON IP video doorphone,APP(Windows、Android/IOS),etc. Built-in mic for full-duplex communication.



Application 2

IP Video Intercom Master Station XC-9037NV support offline video intercom , the offline target need to be added on favorites of device ,when the wireless crashed , the system can normally work.



APPLICATIONS

Application 3

IP Video Intercom Master Station XC-9037NV support multi-party call function and remote door release function ,easy configuration and operation.



DIMENSION DRAWING



CASE



SPON SPON Communications Co., LTD

Address: No.75, Nantaing Road, High-Tech Zone, Changsha, China.
Email: inquiry@cypoecomm.com
Mobile:+86 139 7314 3517
Tel: +86 731 8537 0780